



## TECHNICAL DATA

# SCAPA 3130

## Matte Gaffer Tape

### DESCRIPTION

**Scapa 3130** is a polyethylene coated waterproof cloth tape, single coated with a rubber pressure sensitive adhesive and premium matte finish. This product is available in a full range of colors to meet the demands of the entertainment market.

### APPLICATIONS

- Fixing, bundling and holding of wires and cables
- Color coding and identification
- Floor marking
- Securing scenery or backdrops to different surfaces
- Joining and splicing applications
- Masking applications such as unwanted film set items
- Applications where a matte finish is required to complement appearance

### PRODUCT BENEFITS

- Premium matte finish to prevent the reflection of light, making this product ideal for applications where low light reflectance is essential, especially in theaters, film sets, and studios
- Excellent tear properties
- Removes easily from surfaces without leaving any residue or marks
- Very easy to use in application
- Highly flexible and conformable
- Writable surfaces
- Good strength and all around performance
- Good industrial tack and ultimate adhesion
- Easy unwind

### TECHNICAL PROPERTIES

**Total Thickness**

11.5 mils (.292 mm)

**(800)801-0323** > **www.scapana.com** > **appsupport@scapana.com**

The information given and the recommendations made herein are based on our research and are believed to be accurate but no guarantee of their accuracy is made. In every case we urge and recommend that purchasers, before using any product in full scale production, make their own tests to determine to their own satisfaction whether the product is of acceptable quality and is suitable for their particular purposes under their own operating conditions. **THE PRODUCTS DISCUSSED HEREIN ARE SOLD WITHOUT ANY WARRANTY AS TO MERCHANTABILITY OF FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED.** No representative of ours has any authority to waive or change the forgoing provisions but, subject to such provisions, our engineers are available to assist purchasers in adapting our products to their needs and to the circumstances prevailing in their business. Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

## ADHESIVE TEST DATA

Peel Adhesion	<u>Oz./Inch</u>	<u>(N/25mm)</u>
	30	8
Backing Adhesion	14	4
Tensile Strength	<u>lb./Inch</u>	<u>(N/25mm)</u>
	32	140

## RECOMMENDATIONS

### *Application to Primary Surface:*

*Unwind adhesive film or tape and apply the adhesive side to the mounting surface. Apply firm pressure. Recommended application temperature to achieve best results is 65° F (18° C) or above. Proper bonding may not occur unless adhesive and surface material are both at 65° F (18° C) or above.*

*NOTE: 1. When applying pressure sensitive adhesive films to any surface, be sure that the surface is free from oil or other surface contaminants such as powder, dust, or release agents. Adhesive performance should be carefully checked when used on substrates containing plasticizers.*

*2. Shelf life is one year from date of shipment when stored in a cool dry place below 76° F (24°C). Rolls should be stored on end.*