3M Automotive Acrylic *Plus* Attachment Tape

Part Numbers 06382, 06383, 06384 and 06386 (Black)

IIIII NASCARI.

Technical Data Sheet	September 2004				
	Supersedes Technical Data Sheet dated July 2002				
General Description	3M [™] Automotive Acrylic <i>Plus</i> Attachment Tape Part Numbers 06382-84 and 06386 are .045-inch-thick, black, high performance, double-coated acrylic foam tapes. These OEM-approved tapes are designed for reliable attachment of a wide variety of automotive exterior and interior trim including body side moldings, claddings, rocker panel moldings, wheel flares, bumper trim and most other automotive trim.				
	3M Acrylic <i>Plus</i> Tape is OEM approved, utilizing breakthrough technology recently developed by 3M. With its unique, new high-performance adhesives on both sides, it offers improved adhesion over a variety of conditions, leading to reduced rework and warranty issues, offering the following key performance features:				
	 Superior adhesion build rate to automotive substrates More conformable core gives excellent wet-out (tape contact) Black, high-strength core maintains a thin, consistent bond line Easy liner release 				
	3M Acrylic <i>Plus</i> Tapes part numbers 06382, 06383, 06384 and 06386 are stronger, higher performing, higher stress handling products than other automotive attachment tapes. These tapes offer more robust performance to a wide variety of automotive substrates.				
Typical Applications	A & B pillar trim Luggage rack slats Door edge moldings				
	panels Emblems Wide body side moldings				
	Wheel flares Claddings Rocker panel moldings				
Product Construction	Easy-Release Liner VR-2 High Performance Acrylic Adhesive Black Acrylic Foam VR-1 High Performance Acrylic Adhesive				

Page 2

Physical Properties

Foam	Black acrylic		
Liner color	Red		
Thickness	.045 in. (1,14 mm)		
Package	Clam shell		

Ordering Information	Part Number	Color	Size	Rolls Per Box	Boxes Per Case
	06382	Black	1/2" x 20 yds (12,7 mm x 18,2 m)	1	12
	06383	Black	7/8" x 20 yds (22,2 mm x 18,2 m)	1	12
	06384	Black	1/2" x 5 yds (12,7 mm x 4,57 m)	1	12
	06386*	Black	1/4" x 20 yds (6,35 mm x 18,2 m)	1	12

*Because of narrower width, 06386 is recommended for wheel flares or other less demanding applications.

Other TrimPlease see your 3M catalog or consult your 3M representative for informationAttachmentabout our complete line of automotive attachment tapes and adhesion promoter.And Repair ProductsOr you may visit us at www.3M.com/automotive, then click on "Product Catalog,"
then "3M™ Tapes and Scotch® Tapes," and then "3M™ Automotive Attachment Tapes."

3M[™] Automotive Adhesion Promoter 06396 is recommended for tape bonding to all plastic substrates. Please contact your 3M sales representative with application or performance questions.

Note: All statements, technical information and recommendations herein are based on tests 3M believes are reliable. 3M does not warrant or guarantee the accuracy or completeness of this information.

Warranty and Limited Remedy: This product will be free from defects in material and workmanship at the time of shipment. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If this product is defective, your exclusive remedy and 3M's and seller's sole obligation shall be, at 3M's option, to replace the product or refund the purchase price.

Limitation of Liability: Except as provided above, 3M and seller will not be liable.

3M and Scotch are trademarks of 3M. NASCAR[™] is a registered trademark of the National Association for Stock Car Auto Racing, Inc.



Automotive Aftermarket Division

3M Center, Building 223-6N-01 St. Paul, MN 55144-1000 www.3M.com/automotive



Minimum 30% Post-Consumer Fiber Printed in U.S.A. © 3M 2004 75-3469-7534-7

