

8-DAY ShurRELEASE® CREPE PAPER MASKING TAPE

TYPICAL APPLICATIONS

- Masking of painted surfaces, wood and metal
- Holding plastic or paper drop cloths
- NOTE: Not for use in lacquer applications or on anodized aluminum

ADVANTAGES AND BENEFITS

- UV resistant
- Flexible and conformable
- High shear values for securing drop cloths
- Consistent surface contact for secure holding power
- Resistant to paint bleed

CONSTRUCTION

Overall Grade/Function: 8-day UV resistant

Backing: Crepe paper

Adhesive: Rubber-based

COLOR(S)



Green (GRN)



STANDARD WIDTH(S)

24 mm 36 mm 48 mm 55 mm

STANDARD LENGTH(S)

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	32 oz/in width	3.50 N/10 mm
Thickness	6 mils	0.15 mm
Elongation	9%	9%
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-CP-20-11/20/2013