

14-DAY ShurRELEASE[®] CREPE PAPER MASKING TAPE

TYPICAL APPLICATIONS

- For use on glass, vinyl, metal and wood
- NOTE: Not recommended for use on wallpaper, unpainted wallboard, ceiling tile or with uncured coatings

ADVANTAGES AND BENEFITS

- Removes cleanly up to 14 days
- Good performance for a variety of applications that require easy removal

CONSTRUCTION

Overall Grade/Function: UV resistant

Backing: Crepe paper

Adhesive: Synthetic Rubber

COLOR



Blue (BLU)



STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm 55 mm

Contact your Shurtape sales representative for other available sizes.

STANDARD LENGTH(S)

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	26 lbs/in width	45.5 N/10 mm
Adhesion to Stainless Steel	32 oz/in width	3.50 N/10 mm
Thickness	5.7 mils	0.14 mm
Elongation	7%	7%
Application Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape[®] is a registered trademark of Shurtape Technologies, LLC

Form# TDS-CP27- 09/25/2013