Designed for today's high tech transportation industry (auto, coaches, buses and marine) Metal preparation, painting, coating and gel coat masking Removes cleanly with no adhesive residue in application temperatures to 300 F

ADVANTAGES AND BENEFITS

- No adhesive residue
- Excellent quick stick
- Clean, flat edges
- Excellent adhesion to metals, rubber, plastics and fiberglass
- Strips cleanly with no residue or paint flake after baking and extended application periods
- Solvent resistant
- Excellent adhesion to tape backing and masking papers
- Smooth unwind

CONSTRUCTION

Overall Grade/Function: High Performance Backing: Smooth crepe paper Adhesive: Rubber-based

COLOR(S)

Natural (NAT)

STANDARD WIDTH(S)

STANDARD LENGTH(S)

18 mm 24 mm 36 mm 48 mm 55 m Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	26 lbs/in width	45.5 N/10 mm
Adhesion to Stainless Steel	43 oz/in width	4.71 N/10 mm
Thickness	5.9 mils	0.15 mm
Elongation	9%	9%
Service Temperature Range	45 F to 300 F	7.2 C to 149 C
Distant and a seference of the set of the se	Real address of the second state of the Second	I farme the state of the second s

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC Form# TDS-CP-500-08/20/2014 fiberglass baking and extended application periods



HIGH PERFORMANCE GRADE

TYPICAL APPLICATIONS

HIGH TEMPERATURE MASKING TAPE



