

60-DAY Shurrelease® Razor edge® smooth paper masking tape

TYPICAL APPLICATIONS

• Designed for painting stripes, diamonds and other patterns on walls

ADVANTAGES AND BENEFITS

- Leaves only the sharpest, cleanest lines
- Removes clean up to 60 days in direct sunlight
- Low tack for delicate surfaces
- · Special paper backing reduces bleed-through

CONSTRUCTION

Overall Grade/Function: 60-day UV resistant

Backing: Smooth paper Adhesive: Acrylic

COLOR



STANDARD WIDTH(S)

STANDARD LENGTH(S)

24 mm 36 mm 48 mm 55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.2 N /10 mm
Adhesion to Stainless Steel	14 oz/in width	1.53 N /10 mm
Thickness	3.7 mils	0.09 mm
Elongation	3.9%	3.9%

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.



^{*}Shurtape® is a registered trademark of Shurtape Technologies, LLC Form# TDS-CP60- 09/06/2013