

**PREMIUM GRADE  
PRINTABLE CREPE PAPER MASKING TAPE**

**TYPICAL APPLICATIONS**

- For use on a variety of smooth substrates as a general purpose tape
- Packaging, bundling, binding, holding, splicing & banding
- Labeling, color-coding, decorating, identification

**ADVANTAGES AND BENEFITS**













- Adhesive system designed for excellent performance and adhesion to a variety of smooth substrates
- Resists water, solvents and oil

**CONSTRUCTION**

Overall Grade/Function: Premium  
Backing: Printable colored crepe paper  
Adhesive: Rubber-based



**COLOR(S)**

 Black (BLK)	 Green (GRN)	 Red (RED)	 White (WHI)
 Gray (GRY)	 Purple (PRP)	 Orange (ORG)	 Light Blue (LBL)
 Blue (BLU)	 Yellow (YEL)	 Pink (PNK)	 Light Green (LGR)

**STANDARD WIDTH(S)**

9 mm 12 mm 18 mm 24 mm 48 mm 55 mm

**STANDARD LENGTH(S)**

Contact your Shurtape sales representative for other available sizes.

**PHYSICAL PROPERTIES**

	<b>STANDARD</b>	<b>METRIC</b>
Tensile Strength	22 lbs/in width	38.5 N/10 mm
Adhesion to Stainless Steel	44 oz/in width	4.82 N/10 mm
Thickness	6.1 mils	0.15 mm
Elongation	9%	9%
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

**APPLICABLE STANDARDS**

ASTM D 6123/D 6123M-97 (2012), Type I

**STORAGE & USAGE CONDITIONS**

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC  
Form# TDS-CP-64-08/20/2014