

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Mounting, holding, splicing, tabbing and joining various substrates including metal and plastic
- > Laying carpet
- > Attaching nameplates

ADVANTAGES AND BENEFITS

- > High quality adhesive
- > Double-faced tape without a thick, bulky backing
- > Used on a variety of substrates
- > Excellent resistance to heat, weathering and thermal creep



CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Semi-transparent, tissue paper

Adhesive: High quality acrylic

Liner: Heavy duty, siliconized, flat, paper release liner

COLOR(S)



White (WHI)

STANDARD WIDTH(S)

25 mm 36 mm 50 mm

STANDARD LENGTH(S)

50 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	5.1 lbs/in width	8.9 N/10 mm
Adhesion to Stainless Steel	35 oz/in width	3.83 N/10 mm
Thickness	4.0 mils	0.10 mm
Elongation	2 %	2 %
Service Temperature Range	14 F to 176 F	-10 C to 80 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.