

395



NASHUA®395Multi-Purpose Duct Tape


APPLICATIONS

- Bundling, patching, and mending.
- Packaging.
- Temporary holding & sealing.
- Color coding.

FEATURES & BENEFITS

- · Versatile PE-coated cloth tape.
- Conforms well to irregular surfaces.
- · Adheres well to a variety of substrates.
- Tears straight, hangs straight, curl resistant.
- · Easy unwind.
- Contributes toward satisfying EQ Credit 4.1 (Low Emitting Materials Adhesives & Sealants) under LEED®.

CONSTRUCTION



PRODUCT DESCRIPTION

Single-Coated Construction Backing:

· Polyethylene Coated Cloth

Adhesive:

Rubber

Colors:

 Black, Blue, Brown, Burgundy, Green, Olive Drab, Red, Silver, Tan, White, Yellow

TEST DATA

Test	Typical Value	Typical Value (Metric)	Test Method
Total Thickness	9 mils	228.60 μ	ASTM D 1000
Adhesion to Steel	46 oz./in.	5.03 N/cm	PSTC-1
Adhesion to Backing	45 oz./in.	4.93 N/cm	PSTC-1
Tensile Strength	20 lb./in.	35.03 N/cm	ASTM D 1000
Maximum Performance Temperature	200 F		
VOC Content	<1 g/L		

Recommended storage conditions: 40-60% Humidity, 60°F-80°F

**Products are not reviewed or certified under the LEED[®] Rating System. LEED[®] credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED[®], visit www.usgbc.org/leed.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical person To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all appli federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com Nieuwlandlaan B15 Aarschot Belgium Ph: +32(0)16/55 36 00 Fax: +32 (0)16/55 36 74 4/2/2009