



Backing:	OPP Film
Adhesive:	Acrylic
Liner:	N/A
Colors:	Black Printed or Unprinted
Specifications:	N/A
Standard Sizes:	48mm x 55M

Applications

- Wrapping and protecting foam insulation for pipes and line sets.

Features & Benefits

- OPP Backing
 - Tough and durable.
 - Hand tearable for ease of use.
 - UV Resistant for outdoor installations.
- Acrylic Adhesive
 - Solvent-Free for reduced odor.
 - Aggressive bond - won't flag or lift.
 - Mold and moisture resistant.
- Low VOC Content
 - Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®.

Physical Properties

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.0 mils	76.20 mic	ASTM D-1000
Adhesion to Steel	45 oz/in	4.93 N/cm	PSTC-101
Adhesion to Backing	35 oz/in	3.83 N/cm	PSTC-101
Tensile Strength	32 lb/in	56.04 N/cm	ASTM D-1000
Operating Temperature	0 to 210° F	-17 to 98°C	
VOC Content	<1 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F - 80°F
Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.