



Housewrap Sealing Tape

	Backing Adhesive	Backing:		OPP Film		
		Adhesive	2:	Acrylic		
		Liner:		N/A		
		Colors:	rs: White Printed			
		Specifications: N/A				
		•				
		Standard	i Sizes:	48mm x 50M, 3" x	(5510	
Applications						
Sealing housewrap seams and overlaps. Sealing around window & door flanges & frames						
Sealing exterior wall sheathing joints.			 Patching jobsite damage caused to wall 			
			sheathing and housewraps.			
Features & Benefits						
 OPP Backing Acrylic Adhesive 			Tough and durable.			
			 Hand tearable for ease of use. 			
			• UV Resistant for outdoor installations.			
			• Solvent-Free for reduced odor.			
			 Aggressive bond - won't flag or lift. 			
			 Mold and moisture resistant. 			
			 Used properly, can contribute toward 			
			requirements for EA Credit 1 (Optimize			
			Energy Performance) under LEED [®] .			
			-	Can contribute toward satisfying EQ Credit 4.1		
Low VOC Content			(Low Emitting Materials) under LEED [®] .			
Physical Properties						
	Standa	ard UOM	Metric UOM		Test Method	
Total Thickness	3.0	mils	76.20 mic		ASTM D-1000	
Adhesion to Steel45 oz/in		oz/in	4.93 N/cm	ו	PSTC-101	
Adhesion to Backing 35 oz/in		3.83 N/cm	ו	PSTC-101		
Tensile Strength	32	lb/in	56.04 N/cr	n	ASTM D-1000	
Operating Temperature	e 0 to	210° F	-17 to 98°	C		
VOC Content	<1	g/L				

Recommended Storage Conditions: 40-60% Humidity, 60°F - 80°F Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com Nijverheidsstraat 10 2260 Oevel (Westerlo) Belgium 32-014-722500 Fax 32-014-722570 6/26/2011