



Heavy-Duty

Tarp Tape



- Backing:** Polyethylene Film
- Adhesive:** Rubber
- Liner:** N/A
- Colors:** Black
- Specifications:** N/A
- Standard Sizes:** 48mm x 27M, 48mm x 50M

Applications

- Hanging and seaming heavy tarps for outdoor protection
- Hanging, seaming and splicing poly sheeting
- General bundling & holding
- **Suitable for 6-8 months of outdoor use**

Features

- Black Polyethylene Backing
- Rubber Adhesive

Benefits

- UV resistant for outdoor applications
- Tough & durable
- Conformable
- High tack to bond with tarps and sheeting
- Smooth to provide superior contact between the adhesive and the surface to bond

Physical Properties

	Standard UOM	Metric UOM	Test Method
Total Thickness	7.5 mils	190.5 mic	ASTM D-1000
Adhesion to Steel	42 oz/in	4.6 N/cm	PSTC-101
Tensile Strength	22 lb/in	38.53 N/cm	ASTM D-1000
Elongation	75%		
Operating Temperature	40 - 180° F	4 - 82° C	

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F
 Standard Shelf Life (at 25C): 24 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.