

HOUSEWRAP/SHEATHING TAPE CCMC CERTIFIED

TYPICAL APPLICATIONS

- Closure tape for housewrap material to include repairs and new construction
- Seals seams and joints on all types of housewrap, sheathing, insulation or vapor barrier materials

ADVANTAGES AND BENEFITS

- CCMC Report No: 13401-R
- 1st To Market: Water-based (emulsion) acrylic adhesive
- UV resistant
- Hand-tearable
- Green Point contributor product
- Application usage in vast temperature ranges and humid conditions
- Aggressive adhesive with high shear and holding power capabilities
- Permanent adhesive

CONSTRUCTION

Overall Grade/Function: CCMC Housewrap/Sheathing Tape
Backing: UV Resistant, Red/Red with black print film
Adhesive: Water-based (Emulsion) Acrylic

COLOR(S)



Red with Black Print (RPT)



Red (RED)

STANDARD WIDTH(S)

60 mm

STANDARD LENGTH(S)

66 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	34 lbs/in width	59.5 N/10 mm
Adhesion to Stainless Steel	51 oz/in width	5.58 N/10 mm
Adhesion to Housewrap	26 oz/in width	2.84 N/10 mm
Thickness	3 mils	0.07 mm
Elongation	162%	162%
Application Temperature Range	14 F to 176 F	-10 C to 80 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

CCMC Report No: 13401-R; US Green Building Council – LEED® Point contributor product; Tested in accordance with UL 723; FSI 0/SDI 0

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 24 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.



*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-HW-300-12/19/2013