

# J.V. Converting Company, Inc.

87 Towpath Road Suite 101 • Fairless Hills, PA 19030 • PHONE (215) 428-0763 • FAX (215) 428-0779

## PRODUCT DATA SHEET

### SCF-01

#### SINGLE SIDED LOW DENSITY PVC FOAM TAPE

*Gray and Black*

#### DESCRIPTION

Low density Closed Cell PVC foam coated on one side with a high performance acrylic adhesive. Carried on a white siliconized paper liner. Excellent combination of flexibility and conformability with strength & wear resistance. Excellent weatherability & chemical resistance. It is a clean, waste free substitute for liquid sealants. An economical general purpose foam tape used in applications requiring positive seals on irregular surfaces or when flex and conformability to seal tight radius curves are critical considerations.

#### APPLICATIONS

Used extensively in the automotive, HVAC, and construction industries to provide air & weather tight seals; for gasketing, cushioning, & vibration control in speakers, vehicles, electronic components, doorframes, etc.

#### PHYSICAL PROPERTIES

Foam	PVC
Density (Range)	6 - 10 lb. per cubic foot
Force to Compress 25% (Range)	3.0 - 4.0 psi
Compression Deflection (Range)	1.0 - 2.5 psi
Tensile Strength	Minimum 15 psi
Color	Gray and Black
Adhesive	Acrylic
Service Temperature	-40°F to 180°F
Release Liner	White Siliconized Paper Liner

**NOTE:** The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

0608am