

## **P-02 MULTI-PURPOSE DOUBLE-COATED SPLICING & MOUNTING TAPE**

### **APPLICATION**

A highly versatile double-coated tape that boasts **super-aggressive adhesion**. Designed for a variety of **splicing, mounting, holding, laminating and fastening** applications...especially wherever tape conformability and strength are vital. Ideal for use with glass or metal surfaces, too.

Also recommended for holding metal in place during machining operations for anchoring metal plates, type, cuts and patches to printing forms; and, for mounting small fixtures, display items and moldings. Can be die-cut or shear-cut to any size or shape.

### **FEATURES AND BENEFITS**

- Coated on both sides with an aggressive, synthetic rubber/resin adhesive that makes it ideal for splicing medium-to-heavyweight paper stocks.
- Provides high shear strength, high initial tack.
- Solvent resistant - will not dissolve when exposed for limited periods to solvents such as MEK, carbon tetrachloride, gasoline or alcohol.
- Interliner removes easily...even after exposure to high pressure-laminating operations.

### **TECHNICAL DATA**

Backing material	Flat Kraft paper
Adhesive	Synthetic rubber/resin
Color	White
Tape thickness	
with liner	11.0 mils/0.28 mm
without liner	8.2 mils/0.19 mm
Adhesion to liner	1.8 oz. per in./20.1 gm per cm
Adhesion to steel	81.0 oz. per in./838 gm per cm
Gov't specification	FDA Title 21, Part 175.105 / CID A-A-180

Note: The above are typical values and should not be used in writing specifications.

### **STOCK SIZES**

Refer to current Industrial Division Price List.

**For Additional Information on this Product, Call Toll-Free 1-800-755-TAPE.**