

SPECIALTY GRADE – CAMO CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- Sealing, waterproofing, holding, camouflaging, sound deadening, covering reflective surfaces and patching applications

ADVANTAGES AND BENEFITS

- Official Army ACU digital and lusterless camouflage patterns
- Waterproof backing
- Conformable

CONSTRUCTION

Overall Grade/Function: Specialty

Backing: Polyethylene film with a cloth carrier

Adhesive: Natural rubber



COLOR(S)



Army Digital (CAM)



RT Green (GRN)



RT Brown (BRN)

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.3 N/10 mm
Adhesion to Stainless Steel	40 oz/in width	4.38 N/10 mm
Thickness	10 mils	0.25 mm
Elongation	29%	29%
Service Temperature Range	50 F to 200 F	32 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC-626-08/14/2014