P- 68

PREMIUM GAFFER'S COATED CLOTH TAPE

TYPICAL APPLICATIONS

- Book-binding
- Color-coding
- · Gaffer's applications

ADVANTAGES AND BENEFITS

- High tensile strength
- Waterproof backing
- Abrasion resistant
- Hand tearable
- Matte surface

CONSTRUCTION

Overall Grade/Function: Premium Backing: Acrylic coated cloth Adhesive: Synthetic rubber

COLOR(S)

Black (BLK)

White (WHI)

STANDARD WIDTH(S)

STANDARD LENGTH(S)

1 in 2 in 3 in 60 yd Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	60 lbs/in width	105.1 N/10 mm
Adhesion to Stainless Steel	59 oz/in width	6.46 N/10 mm
Thickness	13.5 mils	0.34 mm
Elongation	5%	5%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

CID A-A 1586A; PM-85-Tested; T-428

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC Form# TDS-P-68-10/01/2014

Shurtape

TRUE TO YOUR WORK