


5068

Polyethylene Greenhouse Patch Tape



Backing: LDPE Film

Adhesive: Acrylic

Liner: N/A

Colors: Clear

Specifications: N/A

Standard Sizes: Incremental widths 1/4" - 54" x 108ft

Applications

- Patching and seaming of greenhouse films
- General purpose sealing, splicing, and patching

Temporary hold down

Features Benefits

•	LDPE Film	Conforms well to irregular surfaces				
		•	Withstandsshort-term exposure to the elements			
		•	Excellent moisture barrier			
		•	Optically clear and hand tearable			
•	Acrylic Adhesive	•	High adhesion and cohesion			
		•	Excellent all temperature performance			
		•	Excellent long-term stability			

Physical Properties

	Standard	Standard UOM		ЮМ	Test Method
Total Thickness	5.5	mils	0.140	mm	PSTC-133
Substrate Thickness	4.5	mils	0.114	mm	PSTC-133
Adhesion to Steel	50	oz/in	5.47	N/cm	ASTM D-3330
Tensile Strength	11	lb/in	19.25	N/cm	ASTM D-3759
Elongation	400%				
Application Temperature	50° F to 120 °F		10° C to 49° C		
Operating Temperature	-40° F to 190 °F		-40° F to 88° C		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 12 months from shipment date

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

