


Preservation & Sealing Tape



Backing: UV Stabilized LDPE Film

Adhesive: Rubber

Liner: N/A

Colors: White

Specifications: N/A

Standard Sizes: Incremental widths 1/4" - 48" x 108ft

Applications

- Long-term preservation, sealing, and splicing
- Direct protective mask on aircraft, trucks, boats, and industrial equipment during outdoor storage
- Splicing, seaming, and sealing polyethylene films
- Used in conjunction with outdoor shrink film to secure film and seal film edges during transport or extended outdoor storage

Features

- LDPE Film
- Rubber Adhesive

Benefits

- Conformable for irregular surfaces
- Abrasion resistant
- UV and weather resistant
- Moisture, solvent, and chemical resistant
- Good quick stick
- Excellent adhesion to PE and shrink film
- Clean removal from most surface
- Resists staining and ghosting
- Excellent low-temperature adhesion

Physical Properties

	Standard UOM		Metric UOM		Test Method
Total Thickness	9.0	mils	0.229	mm	PSTC-133
Substrate Thickness	7.5	mils	0.191	mm	PSTC-133
Adhesion to Steel	34	oz/in	3.72	N/cm	ASTM D-3330
Tensile Strength	17	lb/in	29.75	N/cm	ASTM D-3759
Elongation	500%				
Application Temperature	50° F to 120 °F		10° C to 49° C		
Operating Temperature	-40° F to 200 °F		-40° F to 93 °C		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F
Standard Shelf Life (at 25C): 12 months from shipment date

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

25 Forge Pkwy Franklin, MA 02038
1-800-343-7875 Fax 1-800-328-4822
<http://tapes.berryplastics.com>

4/29/14