

# TECHNICAL DATA SHEET

## INSTRUCTIONS FOR USE OF

# WOOSTER FLOOR PREP

Wooster Floor Prep is an alkaline solvent compound for heavy-duty cleaning.

### PRIMARY APPLICATION

Wooster Floor Prep is an easy to handle, fast cleaning liquid designed for steam or spray cleaning as well as floor scrubbing machines and can be used in both interior and exterior applications. It is designed to clean areas subjected to heavy grease, oil and carbonaceous soils, and can be used to clean any type of surface.

Wooster Floor Prep has been approved by the U.S.D.A. for cleaning floors and walls in poultry, meat, rabbit and egg processing plants.

### CHEMICAL CHARACTERISTICS

Chemical composition	silicates, caustic soda, surface-active agents, water miscible solvents
Physical form	as received: straw colored liquid; as used: water white
Odor	slightly solvent
Specific gravity (approx.)	1.061 ± 0.005 at 20° C (68°F)
Bulk density	9.0 lbs / gal
Flash point	none
Behavior in hard water	sequesters
Biodegradable	yes
Phosphate-free	yes
Foaming tendency	severe
Maximum solubility	infinite
Recommended diluents	water; kerosene or other petroleum derivatives
Normal work concentration	room temperature to 160°F
pH at working concentrations	12.5 to 13.8
Rinsability	excellent
Effect on metals	applicable on steel, stainless steel and magnesium; attacks aluminum, zinc and brass

### **! CAUTION !**      **CLEANING AND APPLICATION PROCEDURE**

Dilute 1/4 pint (4 fl. ounces) of Floor Prep (included in kit) to one gallon of warm-to-hot water (up to 160°F). This amount of solution will clean approximately 30 to 40 square feet of area. Pour the cleaner over the area to be cleaned and allow to soak up to 15 minutes. After soaking, clean area with a power scrubber or agitate with a stiff bristled brush. Agitate until a foaming action occurs. **FOLLOW BY TWO (2) THOROUGH HIGH-PRESSURE WATER RINSES, PREFERABLY HOT.**

In addition, Wooster Floor Prep may be used through foam units, steam detergent cleaning units or spray-type units which provide a non-atomizing spray.

Where heavy soils or extreme oily condition prevail it is recommended that the area be cleaned twice and rinsed again before applying EPOXY WP-70, Safe-Stride Safe-Traction Paint or FLEX-TRED. It is advantageous to use hot solutions up to 160 degrees F and hot water rinses to clean and remove heavy oil and grease.

## NOTES ON USE

**Safety and Handling Precautions:** Floor Prep is a highly alkaline material. Direct contact may cause burns of eyes and skin. It is harmful if swallowed. Avoid contact with eyes, skin and clothing. Wear protective gloves, safety goggles and suitable protective clothing when handling. Wash thoroughly after handling. Do not take internally.

**First Aid in Case of Contact:** Immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, get medical attention. Remove contaminated clothing and shoes. Wash them before reuse. If swallowed, wash out mouth thoroughly with water. Give several glasses of water or milk to drink. Follow with diluted vinegar, lemon juice or other citrus fruit juice. Contact a physician. **KEEP OUT OF REACH OF CHILDREN.**

## STORAGE

Suitable for general storage.

Effect of high temperature storage . . . . . separates (about 120°F) and must be mixed after cooling  
Effect of low temperature storage . . . . . will freeze at 15°F but reconstitutes upon thawing  
Effect of aging . . . . . none

## FOR COMMERCIAL AND INDUSTRIAL USE ONLY

IMPORTANT NOTICE TO PURCHASER: THE FOLLOWING IS MADE IN LIEU OF ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE: Purchase or use of this product constitutes an agreement with Seller and Manufacturer that, if the product proves to be defective or in any way unsuitable, Seller's and Manufacturer's limit of liability for all damages, including but not limited to incidental or consequential damages, and User's or Purchaser's exclusive remedy, regardless of legal theory, including theories of breach of warranty, negligence and strict liability, shall be to receive, at Seller's or Manufacturer's option, repair of the defective product, and equivalent quantity of replacement product or a refund of the purchase price.

# WOOSTER PRODUCTS INC.

Manufacturer of

ABRASIVE SAFETY STAIR TREADS AND WALKWAY PRODUCTS

1000 SPRUCE STREET \* P O BOX 6005 \* WOOSTER, OHIO 44691-6005

TOLL FREE NUMBER: 800-321-4936

PHONE: 330-264-2844 \* FAX: 330-262-4151

Web-Site: <http://www.wooster-products.com>

E-Mail: [Sales@wooster-products.com](mailto:Sales@wooster-products.com)