

P-162 HIGH TENSILE REINFORCED STRAPPING TAPE

APPLICATION

Premium, high tensile strength monofilament glass tape...guarantees **maximum package security for heavy loads**. Engineered to handle practically all strapping applications: palletizing, unitizing, bundling and reinforcing. Plus...it's printable!

FEATURES AND BENEFITS

- Unique adhesive system assures high-hold to boxboard and resistance to carton flap lifting.
- Especially effective with hard-to-hold surfaces. like polyethylene and wax-coated cardboard.
- Polyester/glass construction means real and lasting strength...as well as being waterproof.
- Good clarity. Carton printing can be seen clearly thru tape.
- Remains unaffected by a wide range of chemicals.
- Meets all USDA requirements - may be used as a packaging tape in contact with meat or poultry food products prepared under USDA Federal inspection.
- Government specifications A-A-1687A and PPP-T-97E.

TECHNICAL DATA

Backing material	Polyester film, monofilament glass reinforcement
Adhesive	Synthetic rubber/resin
Color	Clear
Total tape thickness	7.5 mils/0.190 mm
Adhesion to steel	58 oz. per in./624 gm per cm
Tensile strength	
longitudinal	343.5 lbs. per in./64.4 kg per cm
transverse	30 lbs. per in./5.36 kg per cm
Elongation	
longitudinal	5.0%
transverse	90%
Unwind @ 150 FPM	25 oz. per in./280 gm per cm
20° Hold to chrome	Permanent under normal loads
Hold to boxboard	Permanent under normal loads
Boxboard wetting	Delaminates boxboard
Impact strength	65 in.-lbs./0.75 m-kg
Printability	Supplied on special order
FDA status	Meets USDA requirements
Gov't specification	A-A-1687A; PPP-T-97E

Note: The above are typical values and should not be used in writing specifications.

STOCK SIZES

Refer to current Industrial Division Price List.

For Additional Information on this Product, Call Toll-Free 1-800-755-TAPE.