



Safety Data Sheet – Gorilla Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-8-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Gorilla Waterproof Patch and Seal Spray - Black

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Flexible Aerosol Coating

1.3. Supplier

The Gorilla Glue Company
2101 E. Kemper Road
Sharonville, OH 45241
513-271-3300
www.gorillatough.com

1.4. Emergency telephone number

Emergency number : 1-800-420-7186

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable aerosol Category 1	H222	Extremely flammable aerosol
Gases under pressure Compressed gas	H280	Contains gas under pressure; may explode if heated
Acute toxicity (oral) Category 4	H302	Harmful if swallowed
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Carcinogenicity Category 2	H351	Suspected of causing cancer
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child
Specific target organ toxicity (single exposure) Category 3	H336	May cause drowsiness or dizziness
Specific target organ toxicity (single exposure) Category 1	H370	Causes damage to organs
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated



Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Precautionary statements (GHS-US)

- H302 - Harmful if swallowed
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H336 - May cause drowsiness or dizziness
- H351 - Suspected of causing cancer
- H361 - Suspected of damaging fertility or the unborn child
- H370 - Causes damage to organs
- H373 - May cause damage to organs through prolonged or repeated exposure
- P201 - Obtain special instructions before use
- P202 - Do not handle until all safety precautions have been read and understood
- P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- P211 - Do not spray on an open flame or other ignition source
- P251 - Pressurized container: Do not pierce or burn, even after use
- P260 - Do not breathe mist/vapors/spray
- P264 - Wash hands thoroughly after handling
- P270 - Do not eat, drink or smoke when using this product
- P271 - Use only outdoors or in a well-ventilated area
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P301+P312 - If swallowed: Call a poison center/doctor if you feel unwell
- P302+P352 - If on skin: Wash with plenty of water
- P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
- P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P307+P311 - If exposed: Call a poison center/doctor
- P330 - Rinse mouth
- P332+P313 - If skin irritation occurs: Get medical advice/attention
- P337+P313 - If eye irritation persists: Get medical advice/attention
- P362+P364 - Take off contaminated clothing and wash it before reuse
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed
- P405 - Store locked up
- P410+P403 - Protect from sunlight. Store in a well-ventilated place
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
- P501 - Dispose of contents/container in accordance with local, state and federal regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Toluene	(CAS No) 108-88-3	10 – 30*	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Asphalt	(CAS No) 8052-42-4	10 – 30*	Carc. 2, H351
Methyl alcohol	(CAS No) 67-56-1	> 1*	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370
Carbon black	(CAS No) 1333-86-4	0 – 1*	Carc. 2, H351

* Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements: see section 16



Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. Suspected of causing cancer. IF exposed or concerned: Call a POISON CENTER or doctor/physician.
First-aid measures after inhalation	: Assure fresh air breathing. Allow victim to rest. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with water for several minutes. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms	: Harmful if swallowed.
Symptoms/injuries	: Suspected of damaging fertility or the unborn child. Causes damage to organs.
Symptoms/injuries after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

No additional information available

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges.
------------------	---

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel.
----------------------	-----------------------------------

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.



Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Asphalt (8052-42-4)		
ACGIH	ACGIH TWA (mg/m ³)	0.5 mg/m ³ Inhalable fraction
NIOSH	NIOSH REL (ceiling) (mg/m ³)	5 mg/m ³
Methyl alcohol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	6000 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
NIOSH	US-NIOSH chemical category	Potential for dermal absorption
Carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (inhalable fraction)
OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
IDLH	US IDLH (mg/m ³)	1750 mg/m ³
NIOSH	NIOSH REL (TWA) (mg/m ³)	3.5 mg/m ³ 0.1 mg/m ³ (Carbon black in presence of Polycyclic aromatic hydrocarbons)



Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Toluene (108-88-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
IDLH	US IDLH (ppm)	500 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	375 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	560 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm

8.2. Appropriate engineering controls

No additional information available

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Not required under normal conditions. If concentrations exceed exposure limits, use NIOSH approved respirator.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid, aerosol
Color	: Black
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available



Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

Gas group	: Compressed gas
-----------	------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

Waterproof Patch and Seal Spray - Black	
ATE US (oral)	1998.01 mg/kg body weight
Asphalt (8052-42-4)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
Methyl alcohol (67-56-1)	
LD50 oral rat	6200 mg/kg
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h
Toluene (108-88-3)	
LD50 oral rat	636 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
ATE US (oral)	636 mg/kg body weight
ATE US (dermal)	8390 mg/kg body weight



Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Toluene (108-88-3)	
ATE US (vapors)	12.5 mg/l/4h
ATE US (dust, mist)	12.5 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

Asphalt (8052-42-4)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	Twelfth Report - Items under consideration
In OSHA Hazard Communication Carcinogen list	Yes

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity – single exposure	: May cause drowsiness or dizziness. Causes damage to organs.
Specific target organ toxicity – repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Harmful if swallowed.
Symptoms/injuries	: Suspected of damaging fertility or the unborn child. Causes damage to organs.
Symptoms/injuries after inhalation	: Shortness of breath. May cause drowsiness or dizziness.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Methyl alcohol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Toluene (108-88-3)	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	> 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 2	12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])

12.2. Persistence and degradability

Waterproof Patch and Seal Spray - Black	
Persistence and degradability	Not established.



Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Asphalt (8052-42-4)	
Persistence and degradability	Not established.
Carbon black (1333-86-4)	
Persistence and degradability	Not established.
Toluene (108-88-3)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Waterproof Patch and Seal Spray - Black	
Bioaccumulative potential	Not established.
Asphalt (8052-42-4)	
BCF fish 1	(no bioaccumulation expected)
Log Pow	> 6
Bioaccumulative potential	Not established.
Methyl alcohol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77
Carbon black (1333-86-4)	
Bioaccumulative potential	Not established.
Toluene (108-88-3)	
Log Pow	2.65
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapors may accumulate in the container.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT:

Consumer Commodity ORM-D or Limited Quantity

Transport by sea

UN1950, Aerosols, Flammable, 2.1, Ltd. Qty.

Air transport

UN1950, Aerosols, 2.1, Ltd. Qty.





Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

SECTION 15: Regulatory information

15.1. US Federal regulations

Waterproof Patch and Seal Spray - Black

SARA Section 311/312 Hazard Classes

Flammable
Skin corrosion or irritation
Serious eye damage or irritation
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity
Gas Under Pressure

Asphalt (8052-42-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Methyl alcohol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

Carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes

Delayed (chronic) health hazard

Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

SARA Section 311/312 Hazard Classes

Fire hazard
Delayed (chronic) health hazard
Immediate (acute) health hazard

15.2. International regulations

CANADA

Asphalt (8052-42-4)

Listed on the Canadian DSL (Domestic Substances List)

Methyl alcohol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

Carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Asphalt (8052-42-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Methyl alcohol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Carbon black (1333-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on ELINCS (European List of Notified Chemical Substances)

Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations



Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Asphalt (8052-42-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Methyl alcohol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Poisonous and Deleterious Substances Control Law

Carbon black (1333-86-4)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Toluene (108-88-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Poisonous and Deleterious Substances Control Law
Pollutant Release and Transfer Register Law (PRTR Law)

15.3. US State regulations

⚠ WARNING: This product can expose you to toluene, hexane, titanium dioxide and methyl alcohol which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov.

SECTION 16: Other information

Other information

: None.



Safety Data Sheet – Waterproof Patch and Seal Spray- Black

Date Revised: 02-12-2020
Date Issued: 01-08-2020

Version: 1.1

FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.