AC47

12 MIL PREMIUM GRADE **DUCT TAPE**

INTERTAPE POLYMER GROUP®

TECHNICAL DATA SHEET

DESCRIPTION

Polyethylene (PE) coated cloth tape with an aggressive natural rubber, pressure sensitive adhesive for improved adhesion and shear properties. Product is designed to remove cleanly from most surfaces. UV resistant for greater than one week.

PRODUCT APPLICATIONS

Asbestos/lead/fiberglass abatement, exterminators, stucco masking, silk screen mask, plastering, temporary water-proofing, wrapping, bundling, sealing splicing and general maintenance.

GOVERNMENT COMPLIANCE

Tested in accordance with UL-723.

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Backing PE Film

Adhesive Natural Rubber/Resin

Reinforcement PET Cloth

Adhesion to Steel (oz/in of width) 40 (11.0 N/25mm)

PSTC-101

Tensile Strength (lbs/in of width) 45 (197 N/25mm)

PSTC-131

Elongation (% at break) 20

Total Thickness (mils) 12 (0.305mm)

PSTC-133

+32°F to +180°F **Temperature Resistance**

(0°C to +82°C)

Colors Red



100 Paramount Drive, Suite 300 | Sarasota, FL 34232 | USA Customer Service: 800.IPG.8273 | 800.474.8273

Tape Technical Service: 877.447.4832 www.itape.com | info@itape.com

EFFECTIVE: 04/17

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or





