


## 314CRT

## **Cooler Repair Tape**



Backing: **Embossed Foil Laminate** 

Adhesive: Acrylic

Liner: White Kraft Paper

Colors: Silver (Alu), White

Specifications: Tested in accordance with UL723

**Standard Sizes:** 4" x 15yd

## **Applications**

for walk-in refrigeration units, refrigerated display cases and trailers, industrial coolers, and more

Seals seams, cracks, and corners against air leakage • Sealing and patching insulation cladding and jacketing

> **Benefits Features**

Embossed Foil Laminate Backing	Excellent conformability
	<ul> <li>Resists UV, MOLD, and MOISTURE</li> </ul>
	<ul> <li>Zero permeability - provides a superior vapor barrier</li> </ul>
	TOUGH! High strength to resist tear and puncture
All Temperature Acrylic Adhesive	<ul> <li>Withstands very cold and very hot application and operating conditions</li> </ul>
	<ul> <li>Excellent quick stick for an instant seal</li> </ul>
Tested in accordance with UL 723	<ul> <li>Meets flammability and safety requirements for use in refrigeration appliances</li> </ul>
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®</li> </ul>

**Typical Test Values** 

	Standard UOM	Metric UOM	Test Method
Total Thickness	10.2 mils	0.259 mm	PSTC-133
Adhesion to Steel	100 oz/in	10.94 N/cm	PSTC-101
Adhesion to Backing	80 oz/in	8.75 N/cm	PSTC-101
Shear Strength	>72 hours		PSTC-107 @ 2.2 PSI
Tensile Strength	70 lb/in	122.59 N/cm	PSTC-131
Permeance	0.0 perms		ASTM E-96
Puncture Resistance	43 lb	191 N	ASTM D-1000
Operating Temperature	-30 to 270 °F	-34 to132 °C	
Application Temperature	-25 to 248 °F	-32 to 120 °C	
VOC Content	< 30 g/L		

Recommended Storage Conditions: 60 - 80 °F at 40-60% RH Standard Shelf Life (at 25C): 12 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility

