



Polypropylene Surface Protection Tape

Backing	Backing:	Embossed Polypropylene
	Adhesive:	Silicone (S605)
Adhesive	Liner:	N/A
	Colors:	Transparent
	Specifications	: N/A
Single Coated Self Wound	Size Options:	Incremental sizes 1/4in - 58in x 108Ft

Applications					
 Graphics protection for skis, snowboards, and outdoor equipment Sublimation print (170 °C press temp) 	Protective mask for surfaces during lamination, molding, or machining where clean removal is critical				
Features	Benefits				
 Embossed polypropylene backing 	 Conformable and heat resistant Transparent for easy inspection of surfaces Abrasion and moisture resistant 				
Silicone Adhesive	 Does not lift during molding or shaping Smooth, easy unwind Removes cleanly from most surfaces - no residue upon removal Excellent extreme temperature performance 				

Typical Test Values

	Standa	rd UOM	Metric L	MOL	Test Method
Total Thickness	4.3	mils	0.109	mm	PSTC-133
Substrate Thickness	3.5	mils	0.089	mm	PSTC-133
Adhesion to Steel	30	oz/in	3.28	N/cm	ASTM D-3330
Tensile Strength	14	lb/in	24.52	N/cm	ASTM D-3759
Elongation	700%				
Application Temperature	50 to 120 °F		10 °C to 49 °C		
Operating Temperature	-40 to 350 °F		-40 to 176 °C		

Recommended Storage Conditions: 40-60% Humidity, 60 - 80 °F Standard Shelf Life (at 25 °C): 24 months from shipment date

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To BERRY GLOBAL'S knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY GLOBAL assumes any legal responsibility.

