

UGlu® Double-Coated Tape



Technical Data Sheet

**UGlu® is a double-coated tape on a white release liner
with a rubber based adhesive system.**

Features & Benefits:

- Instant bond & permanent hold
- Waterproof & weatherproof
- Can be cleanly removed from most surfaces
- Holds up to 2 lbs.
- Can be cut to size
- Easy-to-peel release liner
- Conforms to uneven surfaces

Technical Data

- ⇒ Adhesive: Rubber
- ⇒ Liner: 60#C2S White SCK Release Liner
- ⇒ Thickness: 20.0 mils
- ⇒ 180° Peel Stainless Steel: 22+ lbs. per inch
- ⇒ Quick Tack (Stainless Steel): 20+ lbs per inch
- ⇒ Shear (1,000 gms @ 72°F): 300+ Hours
- ⇒ Application Temperature: Above 50°F for best performance
- ⇒ Service Temperature: 0°F to 180°F
- ⇒ Chemical Resistance: water, detergent, alcohol. Not recommended for use in contact with aliphatic or aromatic hydrocarbons.
- ⇒ Conforms to ASTM D4236
- ⇒ Acid Free
- ⇒ Non-toxic
- ⇒ VOC Free
- ⇒ UGlu®'s bond is instant. There is no cure or dry time. After strong pressure is applied, the bonding power is at full strength.

Application:

UGlu® can be used to make quick repairs without tools which makes it handy to keep both in-shop and on-site.

Learn more about UGlu® at: www.protapes.com/products/uglu



ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.

UGlu® Double-Coated Tape



Technical Data Sheet

**UGlu® is a double-coated tape on a white release liner
with a rubber based adhesive system.**

Product Characteristics:

UGlu® should not be used in areas where the adhesive is exposed to UV Rays (sunlight). The UV rays will alter the composition of UGlu® and will cause the bond to fail.

UGlu® should not be applied to newly painted surfaces. The painted surface should be allowed to fully cure/dry for 60 days prior to UGlu® application otherwise failure may occur with the bond.

UGlu® Dashes are best used on small applications and on lightweight items including: crafts, kids projects, hanging posters and small decorative accents around the home.

When securing heavier objects, applying larger strips or a 3in x 3in patch will secure your item/s best.

UGlu® should NOT be used on items weighing more than 5 pounds.

UGlu® does not have an expiration date. As long as the protective liners are intact and it is kept in a clean and dry location it can be stored indefinitely.

UGlu® is tacky to the touch however it will NOT permanently bond skin.

Avoid touching UGlu® directly. Direct contact can create balled edges, creases in the adhesive and will increase the chance of grease and oils contaminating the surface.

Caution:

Do NOT use UGlu® on any type of suede covered surfaces.

Do NOT use on valuables, highly sentimental or other irreplaceable items.

Do NOT hang objects over beds.



ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com