

CR 100 PRODUCTION GRADE PAPER PACKAGING TAPE

TYPICAL APPLICATIONS

- For lightweight or non-critical carton sealing applications

PRODUCT FEATURES

- Production grade paper packaging tape
- Curbside Recyclable on the box - using standard application methods
- Medium adhesion
- Hand-tearable
- Utilizes FSC® Certified Paper
- 40% of raw materials come from natural resources

CONSTRUCTION

Backing: Saturated crepe paper

Adhesive: Synthetic rubber-based adhesive

STANDARD WIDTHS

2 in; 3 in

48 mm; 72 mm

STANDARD LENGTH

60.1 yd

55 m

Lead times may apply. Please contact Shurtape customer service for information related to stock and non-stock sizes and colors.

STANDARD CORE SIZE

3 in

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR



PHYSICAL PROPERTIES

	STANDARD	METRIC
Adhesion to Backing	25 oz/in width	2.74 N/10 mm
Adhesion to Kraft	23.8 oz/in width	2.6 N/10 mm
Adhesion to Stainless Steel	51.5 oz/in width	5.64 N/10 mm
Elongation MD	6.5%	6.5%
Service Temperature Range	NA to 150 F	NA to 66 C
Tensile	20 lbs/in width	35 N/10 mm
Thickness	4.3 mils	0.11 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



The mark of responsible forestry
FSC® C154304

*To learn more, visit Shurtape.com/RRQ.