

DF 545

Shurtape®
TRUE TO YOUR WORK™

PREMIUM GRADE, DOUBLE-COATED CLOTH TAPE

TYPICAL APPLICATIONS

- For securing carpet and pad at convention centers, arenas and hotels
- Can also be used for general purpose hanging applications in the construction and abatement industries
- Also used for splicing applications

PRODUCT FEATURES

- Excellent adhesion to smooth and irregular surfaces
- High tensile strength
- Easy to unwind
- Residue-free removal

CONSTRUCTION

Overall Grade/Function: Premium Performance
Backing: Polyester/cotton blend cloth
Adhesive: Rubber-based
Liner: Siliconized, polyethylene release liner

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

23m 33 m

Contact your Shurtape sales representative for other available sizes

APPLICABLE STANDARDS

Meets Consumer Product Safety Commission requirements through conformance with ASTM D-4236

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	24 lbs/in width	42.0 N/10 mm
Adhesion to Stainless Steel	52 oz/in width	5.69 N/10 mm
Thickness (Without Liner)	10.5 mils	0.27 mm
Elongation	8%	8%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

