

tesa® 4124

Product Information



Premium Carton Sealing Tape

Product Description

tesa® 4124 is a premium packaging tape based on a highly durable polyvinylchloride-film backing and a strong natural rubber adhesive. tesa® 4124 is easily printable and available in white, havana, and transparent.

Product Features

- The carton sealing tape shows excellent performance on all kinds of cardboards and ensures a safe closure of mediumand also heavy-weight cartons.
- The tape has a high tensile strength, making it very tearproof.
- tesa® 4124 unwinds smoothly and without noise, which makes it ideal for use in hand dispensers and automatic sealing equipment.
- The process of cardboard waste recycling will be not disrupted, as confirmed by leading recycling companies and paper mills.

Application Fields

- Premium packaging tape tesa® 4124 is used for manual and automatic sealing
- The tape is ideal for application on cartons of medium- to heavy-range weight
- The natural rubber adhesive system ensures an excellent adhesiveness to multiple surfaces
- · The tape has a strong hold and is extremely tearproof

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	PVC film	•	Total thickness	65 μm
•	Type of adhesive	natural rubber			

Properties/Performance Values

•	Elongation at break	60 %	•	Automatic application	yes
•	Tensile strength	60 N/cm	•	Manual application	yes

Adhesion to Values

• Steel 3.2 N/cm



tesa® 4124

Product Information

Additional Information

tesa® 4124 is easy printable. Available colours: white, havana and transparent

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.