



# tesa® Professional 4334 Precision Mask®

## Product Information



High grade paint tape for precise and flat paint edges

### Product Features

- Indoor masking (up to 6 months)
- Outdoor masking (up to 8 weeks)
- For smooth and slightly textured surfaces
- For high-quality painting and lacquering work
- For spray painting with afterwards oven drying up to 120°C/30 min

The tesa® Precision Mask® 4334 reliably guarantees razor-sharp paint edges, and is extremely easy to use at the same time - thanks to the ideal combination of the special, supple backing and the perfectly balanced acrylic adhesive compound. This helps the tape to stick extremely flush to the surface and prevent paint tears. The combination of professional painting tape and your skilled expertise will result in paintwork to please your customers. In addition, the high quality of the painting tape will save you expensive touch-up work. The tesa® Precision Mask® 4334 is also recommended for masking applications during spray painting with afterwards oven drying up to 120°C/ 30min. Due to the thin and low elongating backing it is perfectly suited for two-tone applications, e.g. straight and long lines.

### Product Construction

- |                    |             |         |             |
|--------------------|-------------|---------|-------------|
| • Type of adhesive | acrylic     | • Color | yellow      |
| • Total thickness  | 90 µm       | •       | Washi paper |
| • Backing material | Washi paper |         |             |

### Product Properties/Performance Values

- |                                   |           |                               |           |
|-----------------------------------|-----------|-------------------------------|-----------|
| • Elongation at break             | 4 %       | • Tensile strength            | 30 N/cm   |
| • Conformability                  | very good | • Hand tearability            | very good |
| • Sharp color edge                | very good | • Suitable for rough surfaces | good      |
| • Suitable for sensitive surfaces | good      | • Paint anchorage             | very good |
| • UV-resistance                   | 8 weeks   |                               |           |

### Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 1.8 N/cm |
|---------|----------|



# tesa<sup>®</sup> Professional 4334 Precision Mask<sup>®</sup>

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=04334>