



tesa® Professional 4439

Product Information



Waterproof masking tape for precise and flat paint edges outdoors

Product Features

- Because the adhesive compound and backing material are not only extremely precise, they are also particularly weatherproof and UV-resistant.
- The waterproof masking tape remains stable for a long time in all weathers.
- The paper masking tape is a reliable partner for painting work of all kinds and, combined with sound workmanship, will return excellent results.

The tesa Precision Mask® Outdoor guarantees razor-sharp paint edges for the outdoors. The waterproof masking tape comprises a tear-proof, thin special backing which is coated with an acrylate adhesive compound.

Application Fields

- Outdoor applications
- For long-term applications (up to 8 weeks)*
- Flat, sharp edges to paint and lacquer
- For high-quality painting and lacquering work

*The application of an adhesive tape on weathered surfaces may lead to residues during the de-masking. Thus before using an adhesive tape on a weathered surface we recommend to make a trial application for up to 24 hours.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|--------------------|-------------|
| • Type of adhesive | acrylic | • Backing material | Washi paper |
| • Total thickness | 100 µm | | |

Product Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|---------|
| • Elongation at break | 5 % | • Tensile strength | 35 N/cm |
| • UV-resistance | 8 weeks | | |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 1.8 N/cm |
|---------|----------|

Additional Information

The application of an adhesive tape on weathered surfaces may lead to residues during the de-masking. Thus before using an adhesive tape on a weathered surface we recommend to make a trial application for up to 24 hours.

For latest information on this product please visit
<http://l.tesa.com/?ip=04439>



tesa[®] Professional 4439

Product Information

Additional Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04439>