

Scotch® Film/Fiber Tape 720



Technical Data

April, 2003

Product Description

Scotch® Tape 720 is a semi-transparent tape featuring a high tack, aggressive adhesive and a hand tearable film/fiber backing. It can be used for general purpose sealing and attaching, especially used on treated paper overwraps and other hard-to-stick-to surfaces.

Construction

Backing	Adhesive	Colors
Film/fiber tape	Pressure sensitive rubber resin	Semi-transparent

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	90 oz./in. width (99 N/100 mm width)	D-3330
Longitudinal Tensile Strength:	20 lbs./in. (350 N/100 mm width)	D-3759
Tape Thickness - Backing:	4.5 mil (.114 mm)	D-3652
Total:	6.3 mil (.160 mm)	D-3652
Elongation at Break:	7%	D-3759

Features

- Easily used without the aid of a dispenser.
- Printed data on containers and cartons won't be obliterated.
- Sticks to treated paper overwraps.

Available Sizes

Standard Widths:	1/2 in., 3/4 in., 1 in., 1 1/2 in., 2 in.
Available by Special Order:	Custom widths and lengths available on request, subject to minimum order requirements.
Core Size (ID):	3 in.
Lengths:	72 yds.

Scotch® Film/Fiber Tape

720

Application Techniques An extensive line of manual, semi-automatic and automatic equipment is available to facilitate application of Scotch® Tape 720.

Storage Conditions Storage of Scotch® Tape 720 at 70°F (21°C) and 40-50% relative humidity is recommended.

For Additional Information To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging. Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.

Important Notice 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.

Limitation of Remedies and Liability If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.



This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



Industrial Business
Industrial Adhesives and Tapes Division
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2003 70-0710-0263-1 (4/03)