

**PRODUCTION GRADE
WATER-BASED ACRYLIC BOPP FILM PACKAGING TAPE**

TYPICAL APPLICATIONS

- Automated and manual sealing of light to medium weight cartons

ADVANTAGES AND BENEFITS

- High clarity, low odor, non-yellowing adhesive
- UV resistant

CONSTRUCTION

Overall Grade/Function: Production Grade
Backing: 28 micron biaxially oriented polypropylene cast film
Adhesive: Water-based acrylic adhesive

COLOR(S)



STANDARD WIDTH(S)		STANDARD LENGTH(S)		
48 mm	72 mm	100 m	914 m	1371 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	24 lbs/in width	42.0 N/10 mm
Adhesion to Stainless Steel	22 oz/in width	2.41 N/10 mm
Thickness	2.0 mils	0.05 mm
Elongation	150%	150%
Service Temperature Range	-20 F to 180 F	-29 C to 82 C
Application Temperature Range	20 F to 110 F	-7 C to 43 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

FDA Indirect Contact CFR 21, 175.105*; FDA Indirect Contact CFR 21, 177.1520*

*Clear only

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape[®] is a registered trademark of Shurtape Technologies, LLC

Form# TDS-AP201- 08/29/2014