

BARRICADE TAPE

TYPICAL APPLICATIONS

- Notification of restricted areas
- Manage access to work sites
- Used by professionals in the safety, construction, utilities, hardware and other industries

ADVANTAGES AND BENEFITS

- Resistant to moisture and humidity
- Remains pliant in cold temperature
- Reusable
- 2" letters are easy to read
- Resists sagging for long term use, even when stretched over long distances

CONSTRUCTION

Overall Grade/Function: General Purpose
Backing: Polyethylene plastic
Adhesive: None

COLOR(S)



Danger (RED)



Wet Paint (YEL)



Lead Hazard (WHI)



Caution (YEL)



STANDARD WIDTH(S)

3 in

STANDARD LENGTH(S)

300 ft

1000 ft

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Thickness	2-3 mils	0.05-0.08 mm

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.