

PERFORMANCE GRADE CREPE PAPER MASKING TAPE

TYPICAL APPLICATIONS

- Masking for wood and metal

ADVANTAGES AND BENEFITS

- Flexible and conformable
- Good quick stick
- Strips cleanly in hot or cold environments
- Prevents primer flake-off and paint build-up

CONSTRUCTION

Overall Grade/Function: Performance

Backing: Crepe paper

Adhesive: Rubber-based

COLOR(S)



Natural (NAT)



STANDARD WIDTH(S)

18 mm 24 mm 36 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.7 N/10 mm
Adhesion to Stainless Steel	40 oz/in width	4.37 N/10 mm
Thickness	6.4 mils	0.17 mm
Elongation	9%	9%
Service Temperature Range*	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type I; PPP-T-42C, Type I*

*Standard is obsolete, and provided only as reference

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.