

HVAC UL 181B-FX LISTED FLEX DUCT TAPE

TYPICAL APPLICATIONS

- For use on Class 1 Flex Duct
- Used to connect, join, seal and patch flexible air duct



ADVANTAGES AND BENEFITS

- UL 181B-FX Listed; tested in accordance with UL 723
- Green Point contributor product
- Easy-to-use
- Color matches foil backed flex duct
- Acrylic cold temperature adhesive

CONSTRUCTION

Overall Grade/Function: HVAC/Industrial
Backing: Metalized with Black Print/Black with White Print film
Adhesive: Acrylic

COLOR(S)

-  Black Printed (BPT)
-  Silver Metallic Print (SMT)



STANDARD WIDTH(S) STANDARD LENGTH(S)

48 mm 72 mm 110 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	30 lbs/in width	52.5 N/10 mm
Adhesion to Stainless Steel	38 oz/in width	4.16 N/10 mm
Thickness	2.8 mils	0.07 mm
Elongation	125%	125%
Application Temperature Range	-10 F to 210 F	-23.3 C to 98.9 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

FSI 25/SDI 50; Tested in accordance with UL723; UL 181B-FX; UL Listed; US Green Building Council – LEED® Point contributor product

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 24 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC
Form# TDS-DC-181-08/25/2014