






Multi-Purpose Foil Tape



Backing: 2.0 mil Aluminum Foil

Adhesive: Synthetic Rubber

Liner: Unbleached Natural Kraft Paper

Colors: Aluminum

Specifications: UL 723 Classified

Standard Sizes: 48mm x 46M, 72mm x 46M

Applications

 Taping joints and seams in duct work for A/C, heating, and ventilation systems

- General purpose industrial and automotive uses
- Insulation seaming and patching

Features Benefits

- 2.0 mil Aluminum Foil Backing
- Synthetic Rubber Adhesive
- UL 723 Listed
- Low VOC Content

LEADERSHIP BY DESIGN

- Conformable to fit corners and joints
- UV and moisture resistant
- Mold and mildew resistant
- Non-solvent for less odor and low VOC content
- Extreme high tack, aggressive bond to surfaces
- Good all-weather performance
- Meets flammability requirements for use in construction and marine applications
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Physical Properties

	Standard UOM	Metric UOM	Test Method
Total Thickness	5 mils	127 mic	ASTM D-1000
Foil Thickness	2.0 mils	50.8 mic	ASTM D-1000
Adhesion to Steel	130 oz/in	14.23 N/cm	PSTC-101
Tensile Strength	15 lb/in	26.27 N/cm	ASTM D-1000
Operating Temperature	40-200°F	4-93°C	
Smoke Developed	15		
Flame Spread	10		
VOC Content	<1 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

25 Forge Pkwy Franklin, MA 02038 Nieuwlandlaan B15 Aarschot Belgium 1-800-343-7875 Fax 1-800-328-4822h: +32(0)16/55 36 00 Fax: +32 (0)16/55 36 74 www.covcorp.com 12/16/13