




Extreme Weather FSK Tape



Backing:	Foil/Scrim/Kraft Paper Laminate			
Adhesive:	Acrylic			
Liner:	Unbleached Natural Kraft Paper			
Colors:	Aluminum			
Specifications:		UL 723 Listed & Meets FAR 25.853(a)		
Standard Sizes:		72mm x 46M		

Applications

• Vapor barrier seal for insulation facing

• Sealing insulation and repairing in cooler/ refrigeration applications

Featu	res	Benefits						
• Foil/Scrim/Kraft Laminate	Backing	High strength & tear resistant						
		 UV , moisture a 	nd mold resistant					
High Performance Acrylic	Adhesive	 Non-solvent for less odor and low VOC content 						
		 High tack, aggreet 	essive bond to surfaces					
		 Excellent performance 	rmance in extreme cold or heat					
UL 723 Listed & Meets FA	R 25.853(a).	 Meets flammability requirements for use in 						
		construction, a	erospace and marine applications					
Low VOC Content		Can contribute toward satisfying EQ Credit 4.1						
		(Low Emitting Materials) under LEED®						
Physical Properties								
	Standard UOM	Metric UOM	Test Method					
Total Thickness 6.0 mils		152.4 mic	ASTM D-1000					
Adhesion to Steel 75 oz/in		8.2 N/cm	PSTC-101					

Total Thickness	6.0 mils	152.4 mic	ASTM D-1000
Adhesion to Steel	75 oz/in	8.2 N/cm	PSTC-101
Tensile Strength	30 lb/in	52.53 N/cm	ASTM D-1000
Operating Temperature	-35 to 260° F	-37 to 126° C	
Minimum Application Temp	-25° F	-32° C	
Smoke Developed	0		
Flame Spread	0		
VOC Content	<30 g/L		

Recommended Storage Conditions: 40-60% Humidity, 60°F-80°F Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com Nijverheidsstraat 10 2260 Oevel (Westerlo) Belgium 32-014-722500 Fax 32-014-722570 6/29/2011