

## PACKAGING GRADE KRAFT FLATBACK PAPER TAPE

### TYPICAL APPLICATIONS

- Hand and machine carton sealing
- Splicing of various substrates
- General purpose packaging, binding, holding, tabbing, reinforcing, banding and patching tape for a variety of substrates

### ADVANTAGES AND BENEFITS

- Strong, flexible and conformable backing
- High cross-directional tensile strength
- Aggressive, high-tack adhesive with excellent holding power
- Excellent quick stick, particularly effective in cold weather
- Tape color blends well with kraft cartons
- Resists curling, abrasion, water, solvents and oil
- Good choice for “Shingling” (tape-on-tape)

### CONSTRUCTION

Overall Grade/Function: Packaging  
Backing: Extensible, kraft, flatback paper  
Adhesive: High-tack, rubber-based adhesive



### COLOR(S)



Kraft (KFT)

### STANDARD WIDTH(S)

1¾ in    18 mm    24 mm    36 mm    48 mm    72 mm

Contact your Shurtape sales representative for other available sizes.

### STANDARD LENGTH(S)

60 yd    55 m    439 m

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	36 lbs/in width	63.0 N/10 mm
Adhesion to Stainless Steel	90 oz/in width	9.85 N/10 mm
Thickness	6.1 mils	0.15 mm
Elongation	6%	6%
Service Temperature Range	50 F to 150 F	10 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

ASTM D 6123/D 6123M-97 (2012), Type II

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-FP-96-08/20/2014