

HIGHLY RECYCLED CORRUGATE HOT MELT BOPP FILM PACKAGING TAPE

TYPICAL APPLICATIONS

- For manual (hand rolls) or automatic (machine rolls) case sealing
- Recommended for medium-weight, highly recycled or 100% PCW/OCC cartons
- Packaging, bundling, repairing cartons and paper

ADVANTAGES AND BENEFITS

- High holding power on highly recycled or 100% PCW/OCC cartons
- Tough, aggressive and consistent case sealing performance
- Adheres well to recycled corrugate, recycled paper and a variety of other substrates

CONSTRUCTION

Overall Grade/Function: Production Grade

Backing: 30 micron biaxially oriented polypropylene cast film

Adhesive: Synthetic rubber resin

COLOR(S)



Clear (CLR)



STANDARD WIDTH(S)

48 mm 53 mm 72 mm 100 mm 914 mm 1371 mm

STANDARD LENGTH(S)

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Thickness	2.0 mils	0.05 mm
Tensile Strength (longitudinal)	27 lbs/in width	47.3 N/10 mm
Tensile Strength (transverse)	44 lbs/in width	77 N/10 mm
Elongation	150%	150%
Adhesion to Stainless Steel	55 oz/in width	6.01 N/10 mm
Holding Power to Fiberboard	15,000+ minutes	15,000+ minutes
Application Temperature Range	35 F to 110 F	2 C to 43 C
Service Temperature Range	20 F to 150 F	-7 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

CID A-A-1684C; FDA Indirect Contact CFR 21, 175.105; FDA Indirect Contact CFR 21, 177.1520; ASTM D 1974-98 (2003)

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-HP235- 08/14/2014