

J.V. Converting Company, Inc.

87 Towpath Road Suite 101 • Fairless Hills, PA 19030 • PHONE (215) 428-0763 • FAX (215) 428-0779

PRODUCT DATA SHEET

SCF-02

SINGLE SIDED MEDIUM DENSITY PVC FOAM TAPE *Gray and Black*

DESCRIPTION

A Medium density Closed Cell PVC foam tape coated on one side with a high performance acrylic adhesive. Carried on a siliconized paper liner. Excellent combination of flexibility and conformability with strength & wear resistance. Excellent weatherability & chemical resistance. It is a clean, waste free substitute for liquid sealants.

APPLICATIONS

- Major application: window glazing
- Used for mounting / fixing molding and emblems to various surfaces.
- Vibration dampening, sealing, seaming, and/or gasketing.

PHYSICAL PROPERTIES

Foam	PVC
Density (Range)	13 - 17 lb. per cubic foot
Force to Compress 25% (Range)	6.5 – 9.5 psi
Compression Deflection (Range)	4.0 – 6.0 psi
Tensile Strength	Minimum 45 psi
Color	Gray and Black
Adhesive	Water Based Acrylic
Adhesion (SST) – ASTM D-1000	12oz/inch
Service Temperature	-40°F to 180°F
Release Liner	White Siliconized Paper Liner

NOTE: The physical properties listed above are typical test results obtained from a series of laboratory tests and should not be used for the purpose of writing specifications. Before using this product, user shall determine the suitability of the product for his/her use; and user assumes all risks and liabilities in connection therewith. All test procedures used are in accordance with ASTM and PSTC methods.

0608am