

ShurGRIP™ HEAVY DUTY CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- Heavy duty and temporary to permanent repair cloth duct tape used for industrial, plumbing, HVAC, packaging, bundling, sealing, seaming, repairing, holding and waterproofing
- Used in asbestos-abatement industries
- Excellent shear & adhesion characteristics to poly sheeting, rough surfaces and in colder temperatures

ADVANTAGES AND BENEFITS

- Aggressive adhesion
- Improved holding power to poly-sheeting and steel
- Waterproof backing
- Consistent, low-force unwind off roll

CONSTRUCTION

Overall Grade/Function: Heavy Duty

Backing: Waterproof polyethylene film with a cloth carrier

Adhesive: Natural rubber

COLOR(S)



Silver (SIL)



STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	20 lbs/in width	35.0 N/10 mm
Adhesion to Stainless Steel	120 oz/in width	13.13 N/10 mm
Thickness	9 mils	0.23 mm
Elongation	21%	21%
Service Temperature Range	40 F to 200 F	4.4 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

US Green Building Council – LEED® Point Contributor Product

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC-599-07/23/2014