

## PREMIUM GRADE CLOTH DUCT TAPE

### TYPICAL APPLICATIONS

- Stucco masking
- Motorsports
- Silk screening
- Plastering
- HVAC duct systems
- Bundling, seaming, sealing & splicing


### ADVANTAGES AND BENEFITS

- Waterproof backing
- High tensile strength
- Conformable
- Excellent holding power

### CONSTRUCTION

Overall Grade/Function: Premium Grade  
Backing: Polyethylene film with a cloth carrier  
Adhesive: Natural rubber

### COLOR(S)



### STANDARD WIDTH(S)

48 mm      72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	34 lbs/in width	59.5 N/10 mm
Adhesion to Stainless Steel	56 oz/in width	6.13 N/10 mm
Thickness	12 mils	0.30 mm
Elongation	14%	14%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

Tested in accordance with UL 723; FSI 10/SDI 10; Green Building Council – LEED<sup>®</sup> Point Contributor Product

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape<sup>®</sup> is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC-622-08/20/2014