

MILITARY GRADE, LUSTERLESS CLOTH DUCT TAPE (MIL SPEC PACKAGING TAPE)

TYPICAL APPLICATIONS

- Premium waterproof packaging tape meeting government specifications
- Masking silk screen frames
- To moisture-proof cartons, canisters and tubing

ADVANTAGES AND BENEFITS

- Waterproof backing
- Durable
- Very high holding power
- Conformable
- Lusterless backing
- High tensile strength

CONSTRUCTION

Overall Grade/Function: Military Grade, Lusterless

Backing: Waterproof, polyethylene film with a cloth carrier

Adhesive: Natural Rubber



COLOR(S)



STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	45 lbs/in width	78.8 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness	12.5 mils	0.32 mm
Elongation	12%	12%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

ASTM D 5486M-06, Type IV; PPP-T-60E, Type IV, Class I*

*Standard is obsolete, and provided only as reference

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC-625-08/21/2014