

SPECIALTY GRADE FLOORMATE® TEMPORARY FLOOR TAPE

TYPICAL APPLICATIONS

- Securing protective floor coverings to coated and cured wood floors, residential and commercial
- Gym floor temporary court marking
- Works also on tile and many other floor surfaces

ADVANTAGES AND BENEFITS

- Removes easily - no adhesive residue or lifting of finish on properly prepared floors
- Durable - edge nicks don't easily propagate in backing
- Curved lines - possible due to conformable backing
- Paint masking - capable due to thin, sharp tape edges

CONSTRUCTION

Overall Grade/Function: Specialty

Backing: Modified polyethylene

Adhesive: Acrylic

COLOR(S)



White (WHI)



Black (BLK)



Pink (PNK)

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

60 yd

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	10 lbs/in width	17.5 N/10 mm
Adhesion to Stainless Steel	15 oz/in width	1.64 N/10 mm
Thickness	4.8 mils	0.12 mm
Elongation	332%	332%
Service Temperature Range	32 F to 160 F	0 C to 71 C
Water Vapor Transmission Rate	0.4 gm/100 sq in/24 hr	6.2 gm/msq/24 hr

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

CAUTIONS

Test tape in an inconspicuous area before using. Temporary use only. Finish damage is difficult/expensive to repair on wood floors. Assure preparation and finish application are done per manufacturer's recommendations. Allow finish to cure fully before applying tape. Remove tape slowly prior to 30 days on the floor.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PE-100-10/22/2013



LAB-TESTED FINISHES

WATER-BASED

Absco Grand
Bona Traffic
DuraSeal Polyurethane
General Finishes Enduro
General Finishes High Performance
Hillyard Contender
Loba Hybrid
Loba WS Easyfinish
MINWAX Water-based, Oil-modified
NewAge Full Court Press
Poloplaz Prism

Poloplaz Zenith
Rust-Oleum Pro Finisher
StreetShoe Basic
StreetShoe 275
Varathane Floor Finish
XTerra
Zinsser Nano Shield
Zinsser Polyurethane

SOLVENT-BASED

Defthane Polyurethane
Hillyard 350 Gym Finish