

ULTRA CLEAR, PREMIUM PLUS LABEL PROTECTION & PACKAGING TAPE

TYPICAL APPLICATIONS

- Label protection
- Carton sealing in a broad temperature range
- Over-laminate for instructions, drawings, etc.

ADVANTAGES AND BENEFITS

- High-tack adhesive
- Excellent holding power
- Ultra clear – 100% clarity
- Usable in broad temperature range
- Backing is crystal clear – no streaks, dust or other contaminants

CONSTRUCTION

Overall Grade/Function: Premium Plus

Backing: Crystal clear, biaxially oriented polypropylene film (BOPP)

Adhesive: Ultra clear, solvent-based acrylic

COLOR(S)

Clear (CLR)



STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

50 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	25 lbs/in width	43.8 N/10 mm
Adhesion to Stainless Steel	25 oz/in width	2.74 N/10 mm
Thickness	2.2 mils	0.06 mm
Elongation	150%	150%
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	-20 F to 180 F	-29 C to 82 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

CID A-A-1684C

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PP-803-08/14/2014