

## SPECIALTY GAFFER'S, PHOTO LUMINESCENT COATED CLOTH TAPE

### TYPICAL APPLICATIONS

- Gaffer's tape for various arts and entertainment uses
- Safety marking

### ADVANTAGES AND BENEFITS

- Meets ASTM E 2072 qualifying its use for safety markings in windowless areas
- Cloth substrate is hand tearable in both directions for ease of use and readily conforms to complex 3D surfaces
- Writable/Printable, non-smearing surface provides quick temporary labels and signs that are readable in the dark
- Glows in the dark for unlimited uses and applications
- Premium synthetic rubber adhesive allows for residue free removal
- High adhesion and tack provide strong holding power to most surfaces
- Premium photo luminescent pigment provides increased glow intensity and extended glow duration
- Tested according to LHAMA procedures (see "Applicable Standards" below)



### CONSTRUCTION

Overall Grade/Function: Specialty Gaffer's  
 Backing: Acrylic coated cloth with photo luminescent pigment  
 Adhesive: Synthetic rubber

### COLOR(S)



Glow Green (GLG)

### STANDARD WIDTH(S)

### STANDARD LENGTH(S)

1 in      2 in                      10 yd      20 yd

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	48 lbs/in width	84.1 N/10 mm
Adhesion to Stainless Steel	80 oz/in width	8.76 N/10 mm
Thickness	12.5 mils	0.32 mm
Elongation	5%	5%
Application Temperature Range	45 F to 200 F	7 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE STANDARDS

Conforms to ASTM E 2072; Meets Consumer Product Safety Commission requirements through conformance with ASTM D-4236

This product has been found to conform to the Consumer Product Safety Commissions' (CPSC) "Labeling of Hazardous Art Materials Act" (LHAMA) using a 3rd party toxicologist under ASTM D-4236. LHAMA requires that arts & crafts products sold in the US be reviewed in this manner to determine if any hazardous materials are present through normal product use and to warn consumers if such hazardous materials exist through specific language dictated by a toxicologist. *The statement "Conforms to ASTM D-4236" indicates a toxicologist has reviewed the product and has found no hazardous materials present that would require a warning statement.*

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

\*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-P-661-08/18/2014