

HEAVY DUTY GRADE POLYETHYLENE COATED CLOTH TAPE

TYPICAL APPLICATIONS

- HVAC duct work sealing
- Protection, splicing, bundling, seaming and sealing
- When higher tensile and easy tear are required

ADVANTAGES AND BENEFITS


- High adhesion and tack
- Waterproof backing
- Hand tearable
- Delamination resistant
- Conformable

CONSTRUCTION

Overall Grade/Function: Heavy Duty
Backing: Polyethylene coated cloth
Adhesive: Synthetic rubber



COLOR(S)



STANDARD WIDTH(S)

24 mm 48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	34 lbs/in width	59.5 N/10 mm
Adhesion to Stainless Steel	122 oz/in width	13.35 N/10 mm
Thickness	12 mils	0.30 mm
Elongation	4%	4%
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-P-670-09/22/2014