

Ballroom Carpet Tape

Release Liner Adhesive 2 (Heavy-Duty) Carrier Adhesive 1 (Clean Removal)	Carrier:	Cloth	
	Adhesive:Differential Rubber-Based AdhesiveClean-Removal Air Side - Apply to permanent carpetHeavy-Duty Liner Side - Bonds to temporary carpet backingLiner:Yellow LDPE Film		
	Specification	ns: Low VOC	
	Standard Siz	es: 48mm x 23M	
	Applicatio	ns	

- Temporary carpet installation applications in
 General mounting and holding to floors ٠ ballrooms and other carpeted spaces for tradeshows and conventions
- and carpets where clean removal is required

Features	Benefits
Double-sided Construction	 Easy and fast to install No need to do double work with both a film tape and a carpet tape!
Clean Removal Adhesive (Air Side 1)	 Aggressive adhesion for a secure hold YET REMOVES CLEANLY from most surfaces Repositionable for easy, professional installation
Heavy-Duty Adhesive (Liner Side 2)	 Bonds strong to the underside of carpet

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness*	11.0 mils	0.279 mm	ASTM D-1000
Adhesion to Steel (LS - Heavy-Duty)	60 oz/in	6.56 N/cm	PSTC-101
Adhesion to Steel (AS - Clean Relec	40 oz/in	4.38 N/cm	PSTC-101
Tensile Strength	20 lb/in	35.03 N/cm	ASTM D-1000
Application Temperature	50 to 120 °F	10 to 49 °C	
Operating Temperature	35 to 150 °F	2 to 65 °C	

*Does not include release liner

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%

Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.polyken.com