

PRO FLEX

Patch & Shield Tape



Technical Data Sheet



Pro Flex Patch & Shield Tape is an all weather, flexible butyl patch and shield repair tape. It is the heaviest, most aggressive sealing tape available.

Features & Benefits:

- Colors: White, Black, Grey/ Silver (Special Order)
- UV resistant for assured longevity
- Quick, permanent repair
- All weather application
- Convenient ready to use patch sizes
- Extremely effective in below grade concrete wall penetrations for water
- Stable form -70 F to 200 F
- Conforms Easily
- VOC free

Technical Data

- □ Low temperature flexibility: Excellent
- □ Thickness without liner: 28.0 mils (+/- 2 mils)
- □ Tensile strength: 15 lbs. per inch
- □ 25°F Peel adhesion: 13 lbs. per inch
- □ 150°F Peel adhesion: 2.2 lbs. per inch
- □ WVTR @ 73°F/ 50%rh: <0.02 g / 100in²/ 24hrs
- □ Permanence @ 73°F/ 50%rh: <0.05 perms
- □ Elongation: >700%
- □ Adhesion: 20 lbs per inch
- □ Adhesion to backing: 14 oz./ in
- □ Application Temperature: 20°F to 170°F
- □ Service Temperature: -70°F to 200°F



Application: Pro Flex Tape can be used to reinforce non-leaking seams and for additional security around curbs, vents, chimneys, AC systems, antennas or any roof-penetrating devices. This tape is easy to apply to any clean, dry surface. It is flexible and readily conforms to shapes, making it well suited for gutter repairs, piping or other curved equipment. This product is also recommended for use when stopping leaks on mobile homes, RVs, rail cars, trucks & vans, garden sheds, tarpaulins and some unpressurized piping.

ISO 9001-2008
Certified



621 Route One South. North Brunswick, NJ 08902
Toll Free #1-800-345-0234
sales@protapes.com

Note: The above are typical values and should not be used in writing specifications. The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representatives, guarantees or warranties of any kind are made to the accuracy or suitability for specific applications.